

# Arrow Lock Cylinders



## Mortise Cylinders



### General Specifications

Body – Brass, 1-5/32" (29.37mm) diameter. Six pin tumbler cylinder.  
 Furnished – Standard with cylinder collar.  
 Length-1-1/8" (28.57mm), 1-1/4" (31.75mm), 1-1/2" (38mm), 2" (51mm)  
 Scalp – Brass, Bronze  
 Keyway – "A" keyway standard. Arrow sectional keyways available. Consult factory for competitive keyway availability.

### Finish

US3, US4, US10, US10B, US26, US26D

## Rim Cylinders



### General Specifications

Body – Brass, 1-5/32" (29.37mm) diameter. Six pin cylinder.  
 Furnished – With back plate, 2 Screws (2" door max.), tail-piece and cylinder collar.  
 Scalp – Brass, Bronze  
 Keyway – "A" keyway standard. Arrow sectional keyways available. Consult factory for competitive keyway availability.

### Finish

US3, US4, US10, US10B, US26, US26D

## Cylindrical Lock Cylinders




### General Specifications

Body – Solid brass pin tumbler 6 chambers. Pinned 5 for Grade 2 Locksets. Pinned 6 for Grade 1 locksets and all hotel locksets.  
 Keyway – "A" keyway standard. Arrow sectional keyways available. Competitive keyways available.

### Finish

US4, US26D

## Deadlock Cylinders



### General Specifications

Body – Solid brass pin tumbler, 6 chambers for E & D series deadlocks. E series pinned 5. D series pinned 6.  
 Keyway – "A" keyway standard. Competitive keyways available.

### Finish

US4, US26D

CYLINDER	LOCK	AM/BM	CK	CL	D	E	H	J	K	L	MK	ML	ML	N	Q	RK	RL	S	W	Alarms	Exits
MC61xCam		Std																		I/S	Std
96C (single cylinder)					Opt	Std		Std													
96DC (double cylinder)					Opt	Std															
692C (single cylinder)					Std	Opt		Opt													
692DC (double cylinder)					Std	Opt															
600HD				Std			Std			Std		Std			Std						Std
S600HD																		Std			
100C				Std							Std										
RC62																				O/S	Std
RC63									Std												
C16CR-16/C16CR-27xCam		Std																		I/S	O/S
C16RCR-16/C16RCR-27																				O/S	I/S